Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1-6. (Canceled)
- 7. (Withdrawn) A fuel cell comprising:

an anode;

a cathode; and

an electrolyte membrane disposed between the electrodes, wherein the electrolyte membrane comprises a matrix comprising a proton-conducting polymer and a sheet substantially consisting of an inorganic fiber.

- 8. (Withdrawn) The fuel cell according to claim 7, wherein the anode comprises a catalyst capable of generating hydrogen from methanol.
- 9. (Withdrawn) The fuel cell according to claim 8 which is intended for use in a direct methanol fuel cell.
- 10. (Withdrawn) A method for producing an electrolyte membrane which is intended for use in a fuel cell comprising the steps of:

obtaining a sheet substantially consisting of an inorganic fiber;

obtaining a fluid composition comprising a proton-conducting polymer dissolved or dispersed in a solvent;

impregnating the fluid composition into the sheet; and removing the solvent from the composition.

11. (Withdrawn) A method for producing an electrolyte membrane which is intended for use in a fuel cell comprising the steps of:

obtaining a sheet substantially consisting of an inorganic fiber;

obtaining a fluid composition comprising one or two or more monomers capable of polymerizing to form a proton-conducting polymer;

impregnate the fluid composition into the sheet;

polymerize the monomer or monomers contained in the composition in the above state; and

removing the solvent from the composition.

12. (Withdrawn) A method for suppressing methanol crossover in a fuel cell in which methanol is supplied as fuel comprising the steps of:

obtaining an electrolyte membrane comprising a sheet substantially consisting of an inorganic fiber and a matrix comprising a proton-conducting polymer; and

using the electrolyte membrane as an electrolyte membrane disposed between an anode and a cathode of a direct methanol fuel cell.

- 13. (Withdrawn) The method according to claim 12, wherein a woven cloth or a non-woven cloth consisting substantially of the inorganic fiber is used as the sheet.
- 14. (Withdrawn) The method according to claim 12, wherein an electrolyte membrane is used with at least a portion of the sheet implanted in the polymer matrix.
- 15. (Withdrawn) The method according to claim 12, wherein an electrolyte membrane is used with almost the entire sheet implanted in the polymer matrix.
- 16. (Withdrawn) The method according to claim 12, wherein glass fiber is used as the inorganic fiber.
- 17. (Currently Amended) An electrolyte membrane which is intended for use in a fuel cell comprising:

a matrix comprising a perfluorinated proton-conducting polymer and a sheet having a porosity of 10 10% to 90% by volume and substantially consisting of a glass cloth,

wh	erein the glass cloth is formed by weaving a plurality of glass yarns and
each of the plurality of glass yarns is formed by bundling a plurality of glass fibers, and	
a si	ze of an opening of the glass cloth is between 20 20 μm and 300 μm,
the	entire sheet is implanted in the polymer matrix; and
a th	nickness of a portion of the polymer matrix that has the sheet embedded
therein is between 30% and 80% of the entire thickness of the matrix.	
18. (Cu	arrently Amended) The electrolyte membrane according to claim 17,
wherein a width of each of the plurality of glass yarns constituting the glass cloth is in a range	

of $\underline{10~\mu m}$ to 150 μm when the sheet is viewed from a thickness direction.

19-21. (Canceled)